



- ### GENERAL NOTES
- ALL NORTHERN AND EASTERN ARE AT FACE OF CURB.
 - ALL CONCRETE SHALL BE 3000 PSI @ 28-DAYS WITH FIBER MESH REINFORCEMENT (1.5 LB/CY OF CONCRETE) PER FOOT SPEC #350. CONCRETE SUB-GRADE SHALL BE COMPACTED MINIMUM 95% MODIFIED PROCTOR EXTENDED 12"-IN BELOW CONCRETE BOTTOM.
 - MINIMUM CURB RADI ARE 2 FT.
 - CONTRACTOR SHALL MILL 1/2" OF EXISTING ASPHALT THEN APPLY TACK COAT PRIOR TO RESURFACE MINIMUM 1 1/2" OF ASPHALT.
 - DEDICATED 5 FEET CITY SERVICE EASEMENT ALONG ORANGE BLOSSOM TRAIL SHALL BE SET ASH 25' FROM THE EAST SIDE OF THE TRAIL. THE DEDICATION SHALL BE SET TO FLORIDA DEPARTMENT OF TRANSPORTATION (FDOT) SIDEWALKS PER MEETING ON SEPTEMBER 25, 2009 WITH FOOT (STANLEY CANEY) AND CITY OF ORLANDO (CHARLES BROWN) AND LAW CIVIL ENGINEERING (GUANG LAM).
 - REFER TO SHEET CO - GENERAL NOTES SHEET FOR ADDITIONAL GENERAL NOTES.

REVISIONS

No.	DATE	DESCRIPTION	APP'D BY
1	03-31-09	CITY OF ORLANDO COMM.	QTL
2	05-11-09	ADD OUC NOTES	QTL
3	08-04-09	CITY OF ORLANDO COMM. (BLD2009-03635)	QTL
4	09-18-09	CITY OF ORLANDO BLD2009-00444 COMM.	QTL
5	10-02-09	FDOT UTILITY PERMIT	QTL

FIRST HAITIAN FREE CHURCH OF NAZARENE BY FAITH RENOVATION

GEOMETRY, STRIPING AND SIGNAGE PLAN

Civil Engineering, Inc.
 2504 E. JACKSON STREET
 ORLANDO, FL 32803
 OFFICE: 407-228-9540
 FAX: 407-228-9541

CERTIFICATE OF AUTHORIZATION No. 27340

THIS DOCUMENT AND ANY PERSON DOCUMENTS RELATED TO THIS PROJECT IS THE PROPERTY OF CIVIL ENGINEERING, INC. AND IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED IN THIS DOCUMENT. ANY REPRODUCTION, DISTRIBUTION, OR USE OF THIS DOCUMENT IS PROHIBITED WITHOUT THE WRITTEN CONSENT OF CIVIL ENGINEERING, INC.

NOT FOR CONSTRUCTION UNLESS SIGNED AND SEALED

QUANG T. LAM, P.E.
 FL REGISTRATION NO. 62550

DATE: 11-05-09

PROJECT No. 2008.999.07

DATE: 11-05-09

DRAWN BY: LCE

APPROVED BY: QTL

SHEET C1.1